



Support Bulletin

GEOSPATIAL DIVISION

December 2018

TRIMBLE T10 TABLET: CHANGING THE BATTERY IN THE RAIN

With the Trimble T10 tablet, water can enter the battery compartment when exposed to moisture such as rain. If the battery is inserted and locked correctly in the device, water will not permeate beyond the seal built into the battery.

When the battery is removed from the T10 tablet, both the battery and the tablet can be damaged by water.

When you change the battery, make sure you follow the instructions below to ensure the battery and connectors are not damaged and do not corrode.

Removing the battery

1. Slide the locking clip to the Unlocked position.
2. Push and hold the latch to the left.
3. Lift the battery up and out.

Installing the battery

1. Slide the locking clip to the Unlocked position.

⚠ CAUTION - Make sure the contacts on the T10 tablet, the new battery, and the battery compartment are completely dry prior to replacing battery. If neglected, corrosion may occur.

2. Insert the battery top side first.
3. Press firmly down on the bottom of the battery. The battery latch will flick left then right.
4. Slide the locking clip to the Locked position.

For more information

Contact your local Trimble representative.

www.trimble.com

© 2018, Trimble Inc. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Inc. registered in the United States and in other countries. All other trademarks are the property of their respective owners.